

1.2 Alarm Units

1.2.8 Alarm Unit: FG-A

The FG-A alarm unit is a non-locating unit. It is designed to be used with analog sense cables as FG-ECS, FG-ECX, FG-ACS and FG-ACX for water and acids leak detection.

Responses on the FG-A alarm unit:

- In the case of a leak, an audible alarm is triggered. The red LED on the front panel is switched on and the leak relay is activated.
- In the case of cable break, an audible alarm is triggered, the yellow LED on the front panel is switched on and the cable break relay is acti-




Figure 1: Layout with FG-A

1.2.9 Alarm Unit: FG-A

The FG-A-OD alarm unit is a single sensor alarm unit. It is designed to be used exclusively with FG-OD hydrocarbon range of detectors for oil leak

Responses on the FG-A-OD alarm unit:

- In the case of a leak, an audible alarm is triggered. The red LED on the front panel is switched on and the leak relay is activated.

 In the case of cable break, an audible alarm is triggered, the yellow LED on the front panel is switched on and the cable break relay is acti-




Figure 2: Layout with FG-A-OD



ENGRTEAM.COM

ENGINEER'S

SUPPORT@ENGRTEAM.COM

OWNER:

THE MEAL BOX CAFE

UNIT 5, 120 FENCHURCH, STREET, LONDON, EC3M 5BA

SEAL:

Release for construction

PLUMBING LEAK **DETECTION PLAN**

Drawn by: Engr. Al Amin Checked: Date: